

**SUBLIMATION TRANSFER PAPER ROLL FAST DRY STICKY TACKY 100GSM
ITEM CODE: SPFS6610**

PRODUCT OVERVIEW

Fast dry sticky sublimation paper uses our latest technology, which perfectly meets the needs of users for fast drying and high sticky. The fast-dry sticky paper can print with high ink coverage. It is said to be the best paper there is for adhering to fabric without leaving ghosting and ruining the details of the design. You can expect to eliminate not only your ghosting issues with this paper but your cloudy patterns and blurred images as well.

- ◆ Color: White
- ◆ Length: 100M
- ◆ Width: 610/914/1118/1300/1600/1800mm
- ◆ Weight: 100 g/m²
- ◆ Core Size : 2/3 Inch

APPLICATIONS

- ◆ Textile printing
- ◆ Apparel
- ◆ Towel
- ◆ Sportswear

PROPIEDADES

Drying Time	4 Minutes
Rate of Transfer	≥95%.
Application Temperature	200-220°C
Transfer Time	30-40 seconds



STORAGE OF SUBLIMATION TRANSFER PAPER

Sublimation transfer paper should be stored in a cool and dry place and avoid direct sunlight. It is better to store the paper under constant temperature and humidity in air-conditioned rooms. The ideal storage condition is a relative humidity of 40-70%RH under 10-30°C.

Sticky transfer paper has strong moisture absorption capacity, and its viscosity will change in different temperature and humidity environments. Please be sure to store it in an environment where the relative humidity is less than 70% RH and tie the plastic bag in a cool place away from the light.

PRINTING OF TRANSFER PAPER

The printing environment humidity is preferably controlled at around 45-65% RH, as if the environment is too dry, the transfer paper is curled. Then when printing in large amounts of ink, the transfer paper may arch so it may stretch out and collide into the printing heads and cause malfunctioning. If the environment is too humid, then it may cause the reduction of drying rate of transfer paper and the irregularity of transfer paper's stretch at both ends of the paper. The printing room is recommended to install air-conditioning and dehumidifier to ensure that the printing environment is stable and appropriate.

STORAGE OF PRINTED-PAPER

Keep the paper roll in a loose plastic bag and keep it upright, do not seal the plastic bag so that the moisture from the transfer paper can be evaporated into the air. It is better to store the printed transfer paper in an environment with a humidity of 45-65% RH and a temperature of 15-30°C.



Add: Room 912, No.3 Building, Shangdong Business Center, Haizhou District,
Haining, Zhejiang, China
Tel: +86-573-80776996 Fax: +86-573-80776998
Mob/Skype/Wechat: +86-15858322153
mailto:hncomax@163.com jeffcheung@hncomax.com

