


Features

Vibrantly and consistent printing quality
 Strong durable base fabric
 Great cost-effective
 Matte surface available
 Best suited for indoor/outdoor back-lit displays

Applications



Technical Data Sheet

Item Code		FBCBFX25254040420	Test Method
Base Fabric		250D*250D 40*40	DIN EN ISO2060
Weight (GSM)		420	DIN EN ISO2286-2
Tensile Strength	Warp (N/5cm)	1100	ISO527/3:1995
	Weft (N/5cm)	900	ISO527/3:1995
Tear Strength	Warp (N/5cm)	80	ISO4674/1:2003
	Weft (N/5cm)	70	ISO4674/1:2003
Adhesion Strength		N/A	DIN53357:1982
Temperature		-30°C/+70°C	ISO13934-1:1999
RF Weldable (Heat Sealable)		YES	DIN53354
Flame Retardant		B1/M1/M2/NFPA701	

Information contained in this document is based on our general experience and is given in good faith. But we are unable to accept responsibility in respect to factors which are outside our knowledge or control.

Ink Printability

SOLVENT	ECO-SOLVENT	UV	LATEX	SCREEN PRINTING
■	■	■	■	■



Add: Room 912, No.3 Building, Shangdong Business Center, Haizhou District,
 Haining, Zhejiang, China
 Tel: +86-573-80776996 Fax: +86-573-80776998
 Mob/Skype/Wechat: +86-15858322153
<mailto:contact@hncomax.com> <https://www.hncomax.com>

